

## TECHNICAL DATASHEET

### 1606W // SNOW FIGHTER

|                |                        |
|----------------|------------------------|
| MATERIAL       | Nylon, black           |
| COATING        | Nitrile, sanded, black |
| SIZE(S)        | 8-11                   |
| PACKAGING UNIT | 72 pairs               |
| CERTIFICATION  | EN 388, EN 511         |





### DESCRIPTION

NITRAS SNOW FIGHTER, nylon gloves, black, terry cotton cloth inside, sanded nitrile coating, partly coated on palm and fingertips, black, knitted wrist, highest wearing comfort, highest dexterity

|                        | Material                  | Colour |
|------------------------|---------------------------|--------|
| Palm                   | Nitrile, sanded, on nylon | Black  |
| Index finger and thumb | Nitrile, sanded, on nylon | Black  |
| Back of the hand       | Nylon                     | Black  |
| Fingertips             | Nitrile, sanded, on nylon | Black  |
| Cuff / knitted wrist   | Nylon                     | Black  |

|             |        |       |       |            |
|-------------|--------|-------|-------|------------|
| Size:       | 8      | 9     | 10    | 11         |
| Hem colour: | yellow | brown | black | light blue |

| EN 420:2003 + A1:2009   |                                   | Test parameter | Performance level | Test result |
|---|-----------------------------------|----------------|-------------------|-------------|
|   |                                   | Dexterity      | 1-5               | 5           |
| EN 388:2016   |                                   | Test parameter | Performance level | Test result |
| <br><b>3242X</b> | Abrasion resistance               |                | 1-4               | 3           |
|   | Blade cut resistance (Coupe-Test) |                | 1-5               | 2           |
|   | Tear resistance                   |                | 1-4               | 4           |
|   | Puncture resistance               |                | 1-4               | 2           |
|   | Blade cut resistance (TDM)        |                | A-F               | X           |
| EN 511:2006   |                                   | Test parameter | Performance level | Test result |
| <br><b>X3X</b>   | Convective cold                   |                | 1-4               | X           |
|   | Contact cold                      |                | 1-4               | 3           |
|   | Waterproofness                    |                | 0-1               | X           |