

TECHNICAL DATASHEET

3202 // ARGON



| | |
|----------------|---|
| MATERIAL | Nappa leather, grey Split leather, grey |
| COATING | - |
| SIZE(S) | 9 |
| PACKAGING UNIT | 150 pairs |
| CERTIFICATION | EN 388, EN 407 |



DESCRIPTION

NITRAS ARGON, nappa leather gloves, split leather cuff, length 35 cm, inserted thumb

| | Material | Colour |
|------------------------|---------------|--------|
| Palm | Nappa leather | Grey |
| Index finger and thumb | Nappa leather | Grey |
| Back of the hand | Nappa leather | Grey |
| Fingertips | Nappa leather | Grey |
| Cuff / knitted wrist | Split leather | Grey |

| EN 420:2003 + A1:2009 | | Test parameter | Performance level | Test result |
|--|--|----------------|-------------------|-------------|
| | | Dexterity | 1-5 | 5 |
| EN 388:2016 | | Test parameter | Performance level | Test result |
|  2111X | Abrasion resistance | | 1-4 | 2 |
| | Blade cut resistance (Coupe-Test) | | 1-5 | 1 |
| | Tear resistance | | 1-4 | 1 |
| | Puncture resistance | | 1-4 | 1 |
| | Blade cut resistance (TDM) | | A-F | X |
| EN 407:2004 | | Test parameter | Performance level | Test result |
|  X1XXXX | Resistance to flammability | | 1-4 | X |
| | Contact heat resistance | | 1-4 | 1 |
| | Convective heat resistance | | 1-4 | X |
| | Radiant heat resistance | | 1-4 | X |
| | Resistance to small splashes of molten metal | | 1-4 | X |
| | Resistance to large quantities of molten metal | | 1-4 | X |