

TECHNICAL DATASHEET

4700 // PROTECT PLUS

Material:	Polyethylene / polyester, white
Lining:	-
Size(s):	S-3XL
Packaging unit:	25 pieces
Certification:	EN 14605, EN ISO 13982-1, EN 13034, EN 1149, EN 14126



EN 14605



Type 4-B

EN ISO 13982-1



Type 5-B

EN 13034



Type 6-B

EN 1149



EN 14126



Shell fabric:

65% polyethylene, 35% polyester

Description

NITRAS PROTECT PLUS, chemical protective overall, white, polyethylene / polyester, hood with elastic band, elastic waist, cuffs and ankles, covered zipper, breathable, high-quality workmanship, anti-static properties, type 4-B, type 5-B, type 6-B

	Material	Colour
Shell fabric	65% polyethylene, 35% polyester	white



Do not wash



Do not bleach



Do not tumble dry



Do not iron



Do not dry clean

Kreissparkasse Köln

IBAN: DE06 3705 0299 0127 0022 11
BIC: COKSDE33XXX

Deutsche Bank

IBAN: DE77 3707 0060 0511 1661 00
BIC: DEUTDE33XXX

Postbank Köln

IBAN: DE48 3701 0050 0006 3545 01
BIC: PBNKDEFF


Sparkasse Köln/Bonn


IBAN: DE47 3705 0198 1929 8404 68
BIC: COLSDE33XXX


HypoVereinsbank

IBAN: DE41 3702 0090 0027 7497 47
BIC: HYVEDE33XXX


Es gelten unsere allgemeinen Geschäfts- und Lieferbedingungen (zu finden unter www.nitras.de oder auf Anfrage). Our general terms and conditions of business and delivery apply (can be found at www.nitras.de or on request).

EN 14605:2005 + A1:2009	Test parameter	Test chemicals	Breakthrough time (minutes)
 Type 4-B	Resistance to permeation of liquids	Sulphuric acid 30%	> 480
		Sodium hydroxide 10%	> 480
		o-Xylene	0
		Butan-1-ol	0

EN ISO 13982-1:2004 + A1:2010	Test parameter	Performance level	Test result
 Type 5-B	Abrasion resistance	1-6	3
	Tear resistance (trapezoidal)	1-6	2
	Tensile strength	1-6	3
	Puncture resistance	1-6	1
	Flex cracking resistance	1-6	6
	Seams strength	1-6	3

EN 13034:2005 + A1:2009	Test parameter	Performance level	Test result
 Type 6-B	Repellency against liquids (passed)	1-3	Sulphuric acid 30%: 2 Sodium hydroxide 10%: 3 o-Xylene: 0 Butan-1-ol: 0
	Resistance against penetration of liquids (passed)	1-3	Sulphuric acid 30%: 3 Sodium hydroxide 10%: 3 o-Xylene: 0 Butan-1-ol: 0

EN 1149-5:2008	Test parameter	Performance level	Test result
	Electrostatically dissipative protective clothes	-	-

EN 14126:2003	Test parameter	Performance level	Test result
	Resistance to penetration by contaminated liquids: Synthetic blood	1-6	4
	Resistance to penetration by contaminated liquids: Phi-X174 bacteriophage	1-6	6
	Resistance to penetration by infective agents due to mechanical contact with substances containing contaminated liquids: Staphylococcus aureus	1-6	6
	Resistance to penetration by contaminated aerosols: Staphylococcus aureus	1-3	3
	Resistance to penetration by contaminated solid particles: Bacillus subtilis	1-3	3

Kreissparkasse Köln

IBAN: DE06 3705 0299 0127 0022 11
BIC: COKSDE33XXX

Deutsche Bank

IBAN: DE77 3707 0060 0511 1661 00
BIC: DEUTDE33XXX

Postbank Köln

IBAN: DE48 3701 0050 0006 3545 01
BIC: PBNKDEFF

Sparkasse Köln/Bonn

IBAN: DE47 3705 0198 1929 8404 68
BIC: COLSDE33XXX

HypoVereinsbank

IBAN: DE41 3702 0090 0027 7497 47
BIC: HYVEDEMM429

Es gelten unsere allgemeinen Geschäfts- und Lieferbedingungen (zu finden unter www.nitras.de oder auf Anfrage). Our general terms and conditions of business and delivery apply (can be found at www.nitras.de or on request).